

# SAFETY DATA SHEET

DH5650013

## Section 1. Identification

**Product name** : BERNYL™ STRONG White  
35 Gloss

**Product code** : DH5650013

**Other means of identification** : Not available.

**Product type** : Liquid.

**Relevant identified uses of the substance or mixture and uses advised against**

Paint or paint related material.

**Manufacturer** : AcromaPro Wood Finishes  
101 W. Prospect Avenue  
Cleveland, OH 44115

**National contact** : AcromaPro Wood Finishes  
140 Garden Ave.  
Brantford, ON N3S 7W4

**Emergency telephone number of the company** : US / Canada: (800) 424-9300  
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

**Product Information Telephone Number** : US / Canada: 1-888-277-1448  
Mexico: Not Available

**Transportation Emergency Telephone Number** : US / Canada: (800) 424-9300  
Mexico: SETIQ 800-00-214-00 / 55-5559-1588 Available 24 hours and 365 days a year

## Section 2. Hazards identification

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 2  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A  
CARCINOGENICITY - Category 2  
TOXIC TO REPRODUCTION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1  
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 5.6% (oral), 13.4% (dermal), 15.8% (inhalation)

### GHS label elements

**Hazard pictograms** :



**Signal word** : Danger

**Hazard statements** : Highly flammable liquid and vapor.  
Causes serious eye irritation.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.  
Causes damage to organs through prolonged or repeated exposure. (lungs)

### Precautionary statements

## Section 2. Hazards identification

- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
- Response** : IF exposed or concerned: Get medical advice or attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
- Storage** : Store locked up. Store in a well-ventilated place. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY. Contains Formaldehyde - a potential cancer hazard. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.
- Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
- Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

### CAS number/other identifiers

| Ingredient name                           | % by weight | CAS number |
|---|-------------|------------|
| Titanium Dioxide                          | 25.91       | 13463-67-7 |
| Isobutylated Urea-Formaldehyde Polymer    | 8.55        | 68002-18-6 |
| Ethanol                                   | 6.12        | 64-17-5    |
| Talc                                      | 5.76        | 14807-96-6 |
| n-Butyl Acetate                           | 5.13        | 123-86-4   |
| Xylene, mixed isomers                     | 4.66        | 1330-20-7  |
| Amorphous Silica                          | 2.32        | 7631-86-9  |
| 1-Butanol                                 | 1.9         | 71-36-3    |
| Ethyl 3-Ethoxypropionate                  | 1.7         | 763-69-9   |
| Ethylbenzene                              | 0.84        | 100-41-4   |
| 2-Ethyl-2-(hydroxymethyl)-1,3-propanediol | 0.12        | 77-99-6    |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced fetal weight  
increase in fetal deaths  
skeletal malformations

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## Section 4. First aid measures

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Remark** : Flammable liquid.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 6. Accidental release measures

**Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Contains a formaldehyde-based resin which, under certain conditions of use, may release formaldehyde. Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits (OSHA United States)

| Ingredient name                                   | CAS #                 | Exposure limits  |
|---|-----------------------|--|
| Titanium Dioxide                                  | 13463-67-7            | <b>OSHA PEL (United States, 5/2018).</b><br>TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust<br><b>ACGIH TLV (United States, 1/2024).</b><br>TWA: 2.5 mg/m <sup>3</sup> 8 hours. Form: respirable fraction, finescale particles |
| Isobutylated Urea-Formaldehyde Polymer<br>Ethanol | 68002-18-6<br>64-17-5 | None.<br><b>ACGIH TLV (United States, 1/2024).</b><br>STEL: 1000 ppm 15 minutes.<br><b>NIOSH REL (United States, 10/2020).</b><br>TWA: 1000 ppm 10 hours.<br>TWA: 1900 mg/m <sup>3</sup> 10 hours.                                 |

## Section 8. Exposure controls/personal protection

|   |                      |   |
|---|----------------------|---|
| Talc                                      | 14807-96-6           | <p><b>OSHA PEL (United States, 5/2018).</b><br/>TWA: 1000 ppm 8 hours.<br/>TWA: 1900 mg/m<sup>3</sup> 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020).</b><br/>TWA: 2 mg/m<sup>3</sup> 10 hours. Form: Respirable fraction</p> <p><b>ACGIH TLV (United States, 1/2024).</b><br/>TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</p>  |
| n-Butyl Acetate                           | 123-86-4             | <p><b>NIOSH REL (United States, 10/2020).</b><br/>TWA: 150 ppm 10 hours.<br/>TWA: 710 mg/m<sup>3</sup> 10 hours.<br/>STEL: 200 ppm 15 minutes.<br/>STEL: 950 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL (United States, 5/2018).</b><br/>TWA: 150 ppm 8 hours.<br/>TWA: 710 mg/m<sup>3</sup> 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2024). [Butyl acetates]</b><br/>STEL: 150 ppm 15 minutes.<br/>TWA: 50 ppm 8 hours.</p> |
| Xylene, mixed isomers                     | 1330-20-7            | <p><b>OSHA PEL (United States, 5/2018). [Xylenes]</b><br/>TWA: 100 ppm 8 hours.<br/>TWA: 435 mg/m<sup>3</sup> 8 hours.</p> <p><b>ACGIH TLV (United States, 1/2024). [p-xylene and mixtures containing p-xylene] Ototoxicant.</b><br/>TWA: 20 ppm 8 hours.</p>   |
| Amorphous Silica                          | 7631-86-9            | <p><b>NIOSH REL (United States, 10/2020). [SILICA, AMORPHOUS]</b><br/>TWA: 6 mg/m<sup>3</sup> 10 hours.</p>   |
| 1-Butanol                                 | 71-36-3              | <p><b>ACGIH TLV (United States, 1/2024).</b><br/>TWA: 20 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020). Absorbed through skin.</b><br/>CEIL: 50 ppm<br/>CEIL: 150 mg/m<sup>3</sup></p> <p><b>OSHA PEL (United States, 5/2018).</b><br/>TWA: 100 ppm 8 hours.<br/>TWA: 300 mg/m<sup>3</sup> 8 hours.</p>   |
| Ethyl 3-Ethoxypropionate<br>Ethylbenzene  | 763-69-9<br>100-41-4 | <p>None.</p> <p><b>ACGIH TLV (United States, 1/2024). Ototoxicant.</b><br/>TWA: 20 ppm 8 hours.</p> <p><b>NIOSH REL (United States, 10/2020).</b><br/>TWA: 100 ppm 10 hours.<br/>TWA: 435 mg/m<sup>3</sup> 10 hours.<br/>STEL: 125 ppm 15 minutes.<br/>STEL: 545 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL (United States, 5/2018).</b><br/>TWA: 100 ppm 8 hours.<br/>TWA: 435 mg/m<sup>3</sup> 8 hours.</p>                      |
| 2-Ethyl-2-(hydroxymethyl)-1,3-propanediol | 77-99-6              | None.   |

### [Occupational exposure limits \(Canada\)](#)

## Section 8. Exposure controls/personal protection

| Ingredient name         | CAS #      | Exposure limits   |
|-------------------------|------------|---|
| Ethyl alcohol           | 64-17-5    | <p><b>CA Alberta Provincial (Canada, 3/2023).</b><br/>                     OEL: 1000 ppm 8 hours.<br/>                     OEL: 1880 mg/m<sup>3</sup> 8 hours.</p> <p><b>CA British Columbia Provincial (Canada, 8/2023).</b><br/>                     STEL: 1000 ppm 15 minutes.</p> <p><b>CA Ontario Provincial (Canada, 6/2019).</b><br/>                     STEL: 1000 ppm 15 minutes.</p> <p><b>CA Saskatchewan Provincial (Canada, 4/2021).</b><br/>                     STEL: 1250 ppm 15 minutes.<br/>                     TWA: 1000 ppm 8 hours.</p> <p><b>CA Quebec Provincial (Canada, 2/2024).</b><br/>                     STEV: 1000 ppm 15 minutes.</p>   |
| talc (none asbestiform) | 14807-96-6 | <p><b>CA British Columbia Provincial (Canada, 8/2023). Notes: the value is for particulate matter containing no asbestos and less than 1% crystalline silica.</b><br/>                     TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable</p> <p><b>CA Alberta Provincial (Canada, 3/2023).</b><br/>                     OEL: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate</p> <p><b>CA Ontario Provincial (Canada, 6/2019).</b><br/>                     TWA: 2 mg/m<sup>3</sup> 8 hours. Form: Respirable particulate matter.<br/>                     TWA: 2 f/cc 8 hours.</p> <p><b>CA Quebec Provincial (Canada, 2/2024).</b><br/>                     TWAEV: 2 mg/m<sup>3</sup> 8 hours. Form: respirable aerosol fraction</p> <p><b>CA Saskatchewan Provincial (Canada, 4/2021).</b><br/>                     TWA: 2 mg/m<sup>3</sup> 8 hours. Form: respirable fraction</p>  |
| n-butyl acetate         | 123-86-4   | <p><b>CA Alberta Provincial (Canada, 3/2023).</b><br/>                     OEL: 200 ppm 15 minutes.<br/>                     OEL: 950 mg/m<sup>3</sup> 15 minutes.<br/>                     OEL: 150 ppm 8 hours.<br/>                     OEL: 713 mg/m<sup>3</sup> 8 hours.</p> <p><b>CA Saskatchewan Provincial (Canada, 4/2021).</b><br/>                     STEL: 200 ppm 15 minutes.<br/>                     TWA: 150 ppm 8 hours.</p> <p><b>CA Ontario Provincial (Canada, 6/2019). [butyl acetates, all isomers]</b><br/>                     STEL: 150 ppm 15 minutes.<br/>                     TWA: 50 ppm 8 hours.</p> <p><b>CA British Columbia Provincial (Canada, 8/2023). [butyl acetate, all isomers]</b><br/>                     STEL: 150 ppm 15 minutes.<br/>                     TWA: 50 ppm 8 hours.</p> <p><b>CA Quebec Provincial (Canada, 2/2024). [butyl acetates]</b><br/>                     STEV: 150 ppm 15 minutes.<br/>                     TWAEV: 50 ppm 8 hours.</p> |
| Xylene                  | 1330-20-7  | <p><b>CA Alberta Provincial (Canada, 3/2023).</b></p>   |

## Section 8. Exposure controls/personal protection

|                      |          |  |
|----------------------|----------|--|
| Normal butyl alcohol | 71-36-3  | <p><b>[Dimethylbenzene]</b><br/>         OEL: 100 ppm 8 hours.<br/>         OEL: 651 mg/m<sup>3</sup> 15 minutes.<br/>         OEL: 150 ppm 15 minutes.<br/>         OEL: 434 mg/m<sup>3</sup> 8 hours.<br/> <b>CA British Columbia Provincial (Canada, 8/2023). [Xylene (o, m &amp; p isomers)]</b><br/>         TWA: 100 ppm 8 hours.<br/>         STEL: 150 ppm 15 minutes.<br/> <b>CA Quebec Provincial (Canada, 2/2024). [Xylene]</b><br/>         TWAEV: 100 ppm 8 hours.<br/>         TWAEV: 434 mg/m<sup>3</sup> 8 hours.<br/>         STEV: 150 ppm 15 minutes.<br/>         STEV: 651 mg/m<sup>3</sup> 15 minutes.<br/> <b>CA Ontario Provincial (Canada, 6/2019). [Xylene (o-, m-, p-isomers)]</b><br/>         STEL: 150 ppm 15 minutes.<br/>         TWA: 100 ppm 8 hours.<br/> <b>CA Saskatchewan Provincial (Canada, 4/2021). [Xylene]</b><br/>         STEL: 150 ppm 15 minutes.<br/>         TWA: 100 ppm 8 hours.<br/> <b>CA Alberta Provincial (Canada, 3/2023).</b><br/>         OEL: 60 mg/m<sup>3</sup> 8 hours.<br/>         OEL: 20 ppm 8 hours.<br/> <b>CA British Columbia Provincial (Canada, 8/2023).</b><br/>         TWA: 15 ppm 8 hours.<br/>         C: 30 ppm<br/> <b>CA Ontario Provincial (Canada, 6/2019).</b><br/>         TWA: 20 ppm 8 hours.<br/> <b>CA Saskatchewan Provincial (Canada, 4/2021).</b><br/>         STEL: 30 ppm 15 minutes.<br/>         TWA: 20 ppm 8 hours.<br/> <b>CA Quebec Provincial (Canada, 2/2024).</b><br/>         TWAEV: 20 ppm 8 hours.</p> |
| Ethylbenzene         | 100-41-4 | <p><b>CA Alberta Provincial (Canada, 3/2023).</b><br/>         OEL: 100 ppm 8 hours.<br/>         OEL: 434 mg/m<sup>3</sup> 8 hours.<br/>         OEL: 543 mg/m<sup>3</sup> 15 minutes.<br/>         OEL: 125 ppm 15 minutes.<br/> <b>CA British Columbia Provincial (Canada, 8/2023).</b><br/>         TWA: 20 ppm 8 hours.<br/> <b>CA Ontario Provincial (Canada, 6/2019).</b><br/>         TWA: 20 ppm 8 hours.<br/> <b>CA Quebec Provincial (Canada, 2/2024).</b><br/>         TWAEV: 20 ppm 8 hours.<br/> <b>CA Saskatchewan Provincial (Canada, 4/2021).</b><br/>         STEL: 125 ppm 15 minutes.<br/>         TWA: 100 ppm 8 hours.</p>   |

[Occupational exposure limits \(Mexico\)](#)



## Section 8. Exposure controls/personal protection

| Ingredient name       | CAS #     | Exposure limits   |
|-----------------------|-----------|---|
| Ethanol               | 64-17-5   | <b>NOM-010-STPS-2014 (Mexico, 4/2016).</b><br>STEL: 1000 ppm 15 minutes.  |
| n-Butyl Acetate       | 123-86-4  | <b>NOM-010-STPS-2014 (Mexico, 4/2016).</b><br>TWA: 150 ppm 8 hours.<br>STEL: 200 ppm 15 minutes.                            |
| Xylene, mixed isomers | 1330-20-7 | <b>NOM-010-STPS-2014 (Mexico, 4/2016).</b><br><b>[Xileno, mezcla]</b><br>STEL: 150 ppm 15 minutes.<br>TWA: 100 ppm 8 hours. |
| 1-Butanol             | 71-36-3   | <b>NOM-010-STPS-2014 (Mexico, 4/2016).</b><br><b>Absorbed through skin.</b><br>TWA: 20 ppm 8 hours.                         |

### Biological exposure indices (United States)

| Ingredient name       | Exposure indices  |
|-----------------------|---|
| Xylene, mixed isomers | <b>ACGIH BEI (United States, 1/2024) [xylenes (technical or commercial grades)]</b><br>BEI: 0.3 g/g creatinine, methylhippuric acids [in urine]. Sampling time: end of shift. |
| Ethylbenzene          | <b>ACGIH BEI (United States, 1/2024)</b><br>BEI: 150 mg/g creatinine, sum of mandelic acid and phenylglyoxylic acid [in urine].<br>Sampling time: end of shift.               |

### Biological exposure indices (Canada)

No exposure indices known.

### Biological exposure indices (Mexico)

| Ingredient name       | Exposure indices  |
|-----------------------|---|
| Xylene, mixed isomers | <b>Official Mexican STANDARD NOM-047-SSA1-2011, Environmental Health-Biological exposure indices for personnel occupationally exposed to chemical substances. (Mexico, 6/2012) [xylenes (technical or commercial grade)]</b><br>BEI: 1.5 g/g creatinine, methyl hippuric acids [in urine]. Sampling time: at the end of the work shift. |

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

## Section 8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

- Physical state** : Liquid.
- Color** : White.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not applicable.
- Melting point/freezing point** : Not available.
- Boiling point, initial boiling point, and boiling range** : 77°C (170.6°F)
- Flash point** : Closed cup: 13°C (55.4°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 1.6 (butyl acetate = 1)
- Flammability** : Flammable liquid.
- Lower and upper explosion limit/flammability limit** : Lower: 1%  
Upper: 19%
- Vapor pressure** : 5.9 kPa (44 mm Hg)
- Relative vapor density** : 1.5 [Air = 1]
- Relative density** : 1.36
- Solubility(ies)** :

## Section 9. Physical and chemical properties

| Media      | Result      |
|------------|-------------|
| cold water | Not soluble |

- Partition coefficient: n-octanol/water** : Not applicable.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): >20.5 mm<sup>2</sup>/s (>20.5 cSt)
- Molecular weight** : Not applicable.
- Heat of combustion** : 5.864 kJ/g

## Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
- Incompatible materials** : Reactive or incompatible with the following materials:  
oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

| Product/ingredient name                   | Result                | Species | Dose                     | Exposure |
|---|-----------------------|---------|--------------------------|----------|
| Isobutylated Urea-Formaldehyde Polymer    | LD50 Dermal           | Rabbit  | >5 g/kg                  | -        |
|   | LD50 Oral             | Rat     | >5 g/kg                  | -        |
| Ethanol                                   | LC50 Inhalation Vapor | Rat     | 124700 mg/m <sup>3</sup> | 4 hours  |
|   | LD50 Oral             | Rat     | 7 g/kg                   | -        |
| n-Butyl Acetate                           | LD50 Dermal           | Rabbit  | >17600 mg/kg             | -        |
|   | LD50 Oral             | Rat     | 10768 mg/kg              | -        |
| Xylene, mixed isomers                     | LC50 Inhalation Gas.  | Rat     | 6700 ppm                 | 4 hours  |
|   | LD50 Oral             | Rat     | 4300 mg/kg               | -        |
| 1-Butanol                                 | LC50 Inhalation Vapor | Rat     | 24000 mg/m <sup>3</sup>  | 4 hours  |
|   | LD50 Dermal           | Rabbit  | 3400 mg/kg               | -        |
| Ethyl 3-Ethoxypropionate                  | LD50 Oral             | Rat     | 790 mg/kg                | -        |
|   | LD50 Oral             | Rat     | 3200 mg/kg               | -        |
| Ethylbenzene                              | LD50 Dermal           | Rabbit  | >5000 mg/kg              | -        |
|   | LD50 Oral             | Rat     | 3500 mg/kg               | -        |
| 2-Ethyl-2-(hydroxymethyl)-1,3-propanediol | LD50 Oral             | Rat     | 14000 mg/kg              | -        |

# Section 11. Toxicological information

## Irritation/Corrosion

| Product/ingredient name                        | Result                   | Species              | Score  | Exposure                   | Observation       |
|--|--------------------------|----------------------|--------|----------------------------|-------------------|
| Titanium Dioxide                               | Skin - Mild irritant     | Human                | -      | 72 hours 300 ug l          | -                 |
| Isobutylated Urea-Formaldehyde Polymer Ethanol | Eyes - Severe irritant   | Rabbit               | -      | 24 hours 100 uL            | -                 |
|  | Eyes - Mild irritant     | Rabbit               | -      | 24 hours 500 mg            | -                 |
|  | Eyes - Moderate irritant | Rabbit               | -      | 0.066666667 minutes 100 mg | -                 |
|  | Eyes - Moderate irritant | Rabbit               | -      | 100 uL                     | -                 |
|  | Eyes - Severe irritant   | Rabbit               | -      | 500 mg                     | -                 |
|  | Skin - Mild irritant     | Rabbit               | -      | 400 mg                     | -                 |
|  | Skin - Moderate irritant | Rabbit               | -      | 24 hours 20 mg             | -                 |
|  | Talc                     | Skin - Mild irritant | Human  | -                          | 72 hours 300 ug l |
| n-Butyl Acetate                                | Eyes - Moderate irritant | Rabbit               | -      | 100 mg                     | -                 |
|  | Skin - Moderate irritant | Rabbit               | -      | 24 hours 500 mg            | -                 |
| Xylene, mixed isomers                          | Eyes - Mild irritant     | Rabbit               | -      | 87 mg                      | -                 |
|  | Eyes - Severe irritant   | Rabbit               | -      | 24 hours 5 mg              | -                 |
|  | Skin - Mild irritant     | Rat                  | -      | 8 hours 60 uL              | -                 |
|  | Skin - Moderate irritant | Rabbit               | -      | 100 %                      | -                 |
|  | Skin - Moderate irritant | Rabbit               | -      | 24 hours 500 mg            | -                 |
|  | Amorphous Silica         | Eyes - Mild irritant | Rabbit | -                          | 24 hours 25 mg    |
| 1-Butanol                                      | Eyes - Severe irritant   | Rabbit               | -      | 0.005 MI                   | -                 |
|  | Eyes - Severe irritant   | Rabbit               | -      | 24 hours 2 mg              | -                 |
|  | Skin - Moderate irritant | Rabbit               | -      | 24 hours 20 mg             | -                 |
| Ethyl 3-Ethoxypropionate                       | Skin - Mild irritant     | Rabbit               | -      | 24 hours 500 mg            | -                 |
| Ethylbenzene                                   | Eyes - Severe irritant   | Rabbit               | -      | 500 mg                     | -                 |
|  | Skin - Mild irritant     | Rabbit               | -      | 24 hours 15 mg             | -                 |

## Sensitization

Not available.

## Mutagenicity

Not available.

## Carcinogenicity

Not available.

## Classification

## Section 11. Toxicological information

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| Titanium Dioxide        | -    | 2B   | -   |
| Ethanol                 | -    | 1    | -   |
| Talc                    | -    | 3    | -   |
| Xylene, mixed isomers   | -    | 3    | -   |
| Amorphous Silica        | -    | 3    | -   |
| Ethylbenzene            | -    | 2B   | -   |

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

| Name                  | Category   | Route of exposure | Target organs                |
|-----------------------|------------|-------------------|------------------------------|
| Ethanol               | Category 3 | -                 | Narcotic effects             |
| n-Butyl Acetate       | Category 3 | -                 | Narcotic effects             |
| Xylene, mixed isomers | Category 3 | -                 | Respiratory tract irritation |
| 1-Butanol             | Category 3 | -                 | Narcotic effects             |
|                       | Category 3 | -                 | Respiratory tract irritation |
| Ethylbenzene          | Category 3 | -                 | Narcotic effects             |
|                       | Category 3 | -                 | Narcotic effects             |

### Specific target organ toxicity (repeated exposure)

| Name                  | Category   | Route of exposure | Target organs |
|-----------------------|------------|-------------------|---------------|
| Talc                  | Category 1 | inhalation        | lungs         |
| Xylene, mixed isomers | Category 2 | -                 | -             |
| Ethylbenzene          | Category 2 | -                 | -             |

### Aspiration hazard

| Name                  | Result                         |
|-----------------------|--------------------------------|
| Xylene, mixed isomers | ASPIRATION HAZARD - Category 1 |
| Ethylbenzene          | ASPIRATION HAZARD - Category 1 |

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

# Section 11. Toxicological information

- Inhalation** : Adverse symptoms may include the following:
  - reduced fetal weight
  - increase in fetal deaths
  - skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
  - reduced fetal weight
  - increase in fetal deaths
  - skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
  - reduced fetal weight
  - increase in fetal deaths
  - skeletal malformations

## Delayed and immediate effects and also chronic effects from short and long term exposure

### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

- General** : Causes damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : Suspected of damaging fertility.

## Numerical measures of toxicity

### Acute toxicity estimates

| Route  | ATE value      |
|--------|----------------|
| Oral   | 42125.01 mg/kg |
| Dermal | 35752.92 mg/kg |

# Section 12. Ecological information

## Toxicity

## Section 12. Ecological information

| Product/ingredient name                   | Result                                | Species   | Exposure |
|---|---------------------------------------|---|----------|
| Titanium Dioxide<br>Ethanol               | Acute LC50 >1000000 µg/l Marine water | Fish - <i>Fundulus heteroclitus</i>               | 96 hours |
|   | Acute EC50 17.921 mg/l Marine water   | Algae - <i>Ulva pertusa</i>                       | 96 hours |
|   | Acute EC50 2 mg/l Fresh water         | Daphnia - <i>Daphnia magna</i>                    | 48 hours |
|   | Acute LC50 25500 µg/l Marine water    | Crustaceans - <i>Artemia franciscana</i> - Larvae | 48 hours |
|   | Acute LC50 42000 µg/l Fresh water     | Fish - <i>Oncorhynchus mykiss</i>                 | 4 days   |
|   | Chronic NOEC 4.995 mg/l Marine water  | Algae - <i>Ulva pertusa</i>                       | 96 hours |
|   | Chronic NOEC 100 ul/L Fresh water     | Daphnia - <i>Daphnia magna</i> - Neonate          | 21 days  |
| n-Butyl Acetate                           | Chronic NOEC 0.375 ul/L Fresh water   | Fish - <i>Gambusia holbrooki</i> - Larvae         | 12 weeks |
|   | Acute LC50 32 mg/l Marine water       | Crustaceans - <i>Artemia salina</i>               | 48 hours |
| Xylene, mixed isomers                     | Acute LC50 18000 µg/l Fresh water     | Fish - <i>Pimephales promelas</i>                 | 96 hours |
|   | Acute LC50 8500 µg/l Marine water     | Crustaceans - <i>Palaemonetes pugio</i>           | 48 hours |
| Amorphous Silica                          | Acute LC50 13400 µg/l Fresh water     | Fish - <i>Pimephales promelas</i>                 | 96 hours |
|   | Acute EC50 2.2 g/L Fresh water        | Daphnia - <i>Daphnia magna</i> - Neonate          | 48 hours |
|   | Chronic NOEC 12.5 mg/l Fresh water    | Daphnia - <i>Daphnia magna</i> - Neonate          | 21 days  |
| 1-Butanol                                 | Acute EC50 1983 mg/l Fresh water      | Daphnia - <i>Daphnia magna</i>                    | 48 hours |
| Ethylbenzene                              | Acute LC50 1730000 µg/l Fresh water   | Fish - <i>Pimephales promelas</i>                 | 96 hours |
|   | Acute EC50 4600 µg/l Fresh water      | Algae - <i>Raphidocelis subcapitata</i>           | 72 hours |
|   | Acute EC50 3600 µg/l Fresh water      | Algae - <i>Raphidocelis subcapitata</i>           | 96 hours |
|   | Acute EC50 6.53 mg/l Marine water     | Crustaceans - <i>Artemia sp.</i> - Nauplii        | 48 hours |
|   | Acute EC50 2.93 mg/l Fresh water      | Daphnia - <i>Daphnia magna</i> - Neonate          | 48 hours |
| 2-Ethyl-2-(hydroxymethyl)-1,3-propanediol | Acute LC50 4200 µg/l Fresh water      | Fish - <i>Oncorhynchus mykiss</i>                 | 96 hours |
|   | Acute EC50 13000000 µg/l Fresh water  | Daphnia - <i>Daphnia magna</i>                    | 48 hours |
|   | Acute LC50 14400000 µg/l Marine water | Fish - <i>Cyprinodon variegatus</i>               | 96 hours |

### Persistence and degradability

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| Ethanol                 | -                 | -          | Readily          |
| n-Butyl Acetate         | -                 | -          | Readily          |
| Xylene, mixed isomers   | -                 | -          | Readily          |
| 1-Butanol               | -                 | -          | Readily          |
| Ethylbenzene            | -                 | -          | Readily          |

### Bioaccumulative potential

| Product/ingredient name                   | LogP <sub>ow</sub> | BCF         | Potential |
|---|--------------------|-------------|-----------|
| Xylene, mixed isomers                     | -                  | 8.1 to 25.9 | Low       |
| 2-Ethyl-2-(hydroxymethyl)-1,3-propanediol | -                  | <1          | Low       |

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.






Other adverse effects : No known significant effects or critical hazards.

|                                |                                  |                        |             |         |                  |       |
|--------------------------------|----------------------------------|------------------------|-------------|---------|------------------|-------|
| Date of issue/Date of revision | : 12/13/2024                     | Date of previous issue | : 10/5/2024 | Version | : 33             | 15/18 |
| DH5650013                      | BERNYL™ STRONG White<br>35 Gloss |                        |             |         | SHW-85-NA-GHS-CA |       |

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                   | <b>DOT<br/>Classification</b>   | <b>TDG<br/>Classification</b>  | <b>Mexico<br/>Classification</b>  | <b>IATA</b>   | <b>IMDG</b>   |
|-----------------------------------|---|--|---|---|---|
| <b>UN number</b>                  | UN1263  | UN1263   | UN1263  | UN1263  | UN1263  |
| <b>UN proper shipping name</b>    | PAINT   | PAINT  | PAINT   | PAINT   | PAINT   |
| <b>Transport hazard class(es)</b> | 3<br> | 3<br>  | 3<br> | 3<br> | 3<br> |
| <b>Packing group</b>              | II  | II   | II  | II  | II  |
| <b>Environmental hazards</b>      | No.   | No.  | No.   | No.   | No.   |
| <b>Additional information</b>     | -<br><br><b>ERG No.</b><br>128  | Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).<br><b>ERG No.</b><br>128 | -<br><br><b>ERG No.</b><br>128  | -   | <b>Emergency schedules</b> F-E, S-E   |



## Section 14. Transport information

**Special precautions for user** : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

**Transport in bulk according to IMO instruments** : Not available.

**Proper shipping name** : Not available.

## Section 15. Regulatory information

### International regulations

#### Montreal Protocol

Not listed.

#### Stockholm Convention on Persistent Organic Pollutants

Not listed.

#### International lists

: **Australia inventory (AIIIC)**: Not determined.  
**China inventory (IECSC)**: Not determined.  
**Japan inventory (CSCL)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.  
**Korea inventory (KECI)**: Not determined.  
**New Zealand Inventory of Chemicals (NZIoC)**: Not determined.  
**Philippines inventory (PICCS)**: Not determined.  
**Taiwan Chemical Substances Inventory (TCSI)**: Not determined.  
**Thailand inventory**: Not determined.  
**Turkey inventory**: Not determined.  
**Vietnam inventory**: Not determined.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

|                  |   |   |
|------------------|---|---|
| Health           | * | 3 |
| Flammability     |   | 3 |
| Physical hazards |   | 0 |
|                  |   |   |

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

**Caution:** HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

[Procedure used to derive the classification](#)

# Section 16. Other information

| Classification  | Justification   |
|---|---|
| FLAMMABLE LIQUIDS - Category 2<br>SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A<br>CARCINOGENICITY - Category 2<br>TOXIC TO REPRODUCTION - Category 2<br>SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 | On basis of test data<br>Calculation method<br>Calculation method<br>Calculation method<br>Calculation method |

**History**

**Date of printing** : 12/13/2024

**Date of issue/Date of revision** : 12/13/2024

**Date of previous issue** : 10/5/2024

**Version** : 33

**Key to abbreviations** : ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
N/A = Not available  
SGG = Segregation Group  
UN = United Nations

Indicates information that has changed from previously issued version.

**Notice to reader**

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.